

USASPEC DF-TOY TOYOTA/ISUZU/SCION AUXILIARY INPUT OWNER'S MANUAL

KEY FEATURES

The DF-TOY auxiliary input adapter is designed to interface the audio outputs from devices such as XM radio receivers, DVD players, digital music players, iPods, games and etc directly to Toyota factory audio systems with CD Changer controls. The DF-TOY interface adapter has two AUX input ports namely AUX1 and AUX2 respectively. It is therefore able to interface two independent external audio sources to your factory radio.

The DF-TOY takes the place of the external CD Changer and therefore it is not possible to have a 6-disc CD Changer and the DF-TOY simultaneously connected to the factory radio.

Note: Installing the DF-TOY will not interfere with the operation and controls of Toyota in-dash 6 disc- CD Changer radio.

1. Direct connection of the audio device to Toyota vehicle audio system for optimum sound quality
2. Dual input selectable from the radio
3. Plug-n-play installation – no wire cutting or splicing

1. COMPATIBILITY

TOYOTA	SCION	ISUZU
1998-06 4-Runner	2004-06 xA	1998-03 Amigo
1998-06 Avalon	2004-06 xB	1998-03 Rodeo
1998-06 Camry/Solara	2005-06 tC	1998-03 Trooper
1998-06 Corolla/Echo		
2001-06 Highlander		
1998-01 Land Cruiser		HONDA
2005-06 Matrix		1998-02 Passport†
1998-06 Rav4		
1998-06 Sequoia/Tundra		
1998-06 Sienna		
1998-06 Tacoma		

†Not compatible with in-dash CD changer radio

Not compatible with vehicles that are equipped with external cd changer, SAT, NAV or Video system.

2. PACKAGE CONTENTS

DF-TOY interface adapter
 CAS-TYi Cable
 CAS-TA cable
 Mounting Screws x4

3. INSTALLATION

1. Remove the factory radio
2. Disconnect existing CD Changer from radio if there is one.
3. Connect the CAS-TYi 12-Pin plug to the receptor on the back of the radio. Recent Toyota and Scion vehicles will need to use the CAS-TA Y-adapter. (Connect the CAS-TA Y-adapter male plug to the back of the radio, then connect the CAS-TYi to the matching connector on the other end of the CAS-TA)
4. Connect the round DIN plug on the other end of the CAS-TYi to the DF-TOY connector labeled "RADIO"
5. Connect the audio output from your auxiliary device to the AUX1 or /and AUX 2 input jacks on the DF-TOY
6. Reinstall the factory radio

4. OPERATIONS

Turn on your radio and press "CD" button. The radio will display "**CD 6 Track 1**", "**CD 6 Track 1**" gives access to "AUX1" port of the DF-TOY and "**CD6 Track2**" gives access to AUX2 port of the DF-TOY. Use the track **UP/DOWN** buttons to switch between AUX1 and AUX2.

Adjust the VOLUME, BASS, TREBLE and etc, as you would normally do for the other program sources on the radio.

Revised 2/19/06

© 1995-06 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

Toyota is a registered trade mark of Toyota Motor Corporation.
 Design and specifications are subject to change without notice