



IL-CR12

QUICK START IOS DEVICE INSTALLTION GUIDE TO PORSCHE CR-1 & CR-2 RADIOS

Created: March 21, 2017

Revised: May 1, 2023

PRODUCT SAFETY & DISCLAIMER

READ ALL INSTRUCTIONS CAREFULLY BEFORE INSTALLING, FAILURE TO DO SO MAY CAUSE PERSONAL INJURY OR DAMAGE TO PRODUCT AND/OR PROPERTY

- This installation guide is provided as a GENERAL installation guide, some vehicles vary and may require additional steps. We do not accept responsibility for third party labor charges or modifications. Exercise due-diligence when installing this product.
- We do not accept any responsibility for vehicle damage or personal injury resulting from the installation of this product.
- Careless installation and operation can result in equipment damage.

Requirement:

PORSCHE CR-1 or CR-2 RADIO

Introduction:

Those adamant about keeping their vehicle's stock radio, we offer a simple upgrade allowing factory radio to support new technology. The IL-CR12 allows Porsche CR-1 & CR-2 cassette radios in the 911, 944, 964, 968, 993 to charge and play music files from Apple's latest iPods, iPhones and Tablets including iPhone 5- 14+ etc. Because this adapter connects directly to the radio "CD" port, sound quality is exceptional and factory CD changer (if present), must be disconnected. To retain CD changer, purchase our [A2D-CR12](#) instead.

Installation:

Radio removal required in order to install this part.

Unlike other Porsche radios, the CR-1 and CR-2 radios do not require special tools. To remove:

1. Pry off plastic trim ring around radio. (This exposes mounting points)
2. Locate flat plate with latch on either side of radio. These plates drop down and lock the radio into frame. (See **Fig. 1**)



Fig. 1

3. Use small flat head screwdriver or similar to raise plate (both sides) and simultaneously pull radio out from the dash. Grasping cassette opening provides some leverage or remove glovebox to push radio from rear.
4. If present, disconnect CD changer plug from radio
5. Connect module 13-pin plug (See **Fig. 2**) to radio socket (See **Fig. 3/4**)



Fig. 2



Fig. 3



Fig. 4

6. Run/route IOS lightning plug (See Fig. 5) to desired location on dashboard, glove box, console etc. (within 4 ft. of radio). **Use caution to not cut, pinch or crimp lightning cable during this step.**



Fig. 5

7. Secure IOS lightning cable in a location away from heat, humidity, moving parts, or sharp metal objects. **Damage to lightning plug may occur if subject to abuse.**

Operation:

1. Turn ignition and radio "ON"
2. Connect IOS device to lightning plug
3. IOS device should begin charging
4. Press radio "CD" button to enter "CD" mode (See Fig. 6)



Fig. 6

5. Select track or music application on IOS device

WARNING: Playlist and Track selection *NOT* possible from radio. You must use IOS device built-in controls/display to access music files

6. IOS device playback should now be heard on car speakers
7. Use radio tone controls and volume dials to select playback volume
8. If successful go ahead and reinstall radio

Important:

1. Works only on CR-1 and CR-2 radios. Porsche CD-1, CD-2, CD-10 do NOT apply.
2. Apple device requires power for playback/charge. Ensure ignition key and radio are in the "ON" position.
3. If IOS device plays through built-in speaker; disconnect and reconnect Lightning plug.
4. Not for Nano 7G

Disclaimer

- This product has no affiliation with Porsche etc.
- There are no warranties expressed or implied by purchase of this product
- We're not liable for misuse of this product.
- We recommend professional installation.

Email support@discountcarstereo.com

© 1995-Dec-22 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.