

Courtesy of:DiscountCarStereo.com



CHRY02-AUX

Quick Start Installation Guide for Chrysler CD Changer Ready Radios

created August 10, 2015

Revised: August 6, 2019

Introduction:

Many older car owners who are adamant about keeping the factory radio will be pleased to know that by adding this adapter they are able to play audio devices through their existing radio. The CHRYD2-AUX auxiliary input adapter connects to the radios 10-pin CD Changer/Sat Radio port which guarantees to best possible sound.

See Frequently Asked question at the end of this guide for details.

Installation:

Radio removal required to gain access to connectors.

Vehicle specific radio removal is not part of this guide; however, they are available upon request. With radio out:

1. Disconnect factory option connected to radio 10-pin port (if present)
2. Connect 10-pin gray plug (See **Fig. 1**) from adapter harness to 10-pin connector on radio (See **Fig. 2**)



Fig. 1
10-pin plug



Fig. 2
Radio connectors

3. Connect one end of supplied 3.5mm audio cable (See **Fig. 3**) to input jack on adapter (See **Fig. 4**), route other end to front of the dash or wherever audio device will reside (within 3 ft.)



Fig. 3
3 ft. Aux cable



Fig. 4
3.5mm jack

4. Secure adapter box and proceed to next step.

Test Operation:

1. Turn ignition and Radio "ON"
2. Press "MODE" button until **DI TRI** is displayed (See Fig. 5)



Fig 5

Chrysler rounded face radio with Mode button

3. Turn radio volume control button to set the playback level.

Warning! Use the smartphone built-in controls to access and control audio files or applications.

4. If correct operation is confirmed go ahead and reinstall Radio.

Frequent asked questions

1. **Will the CHRY02-AUX work on all Chrysler 10-pin Radios?**
NO; Works on Chrysler CD Changer Ready Radios with "MODE" button, **DISC UP** on Preset #1 (these indicate radio is Changer Ready)
2. **My Radio has a "rounded face" and CD-C button. Will the CHRY02-AUX work?**
NO, Radios with CD-C button have an 8-pin Changer port and requires the **CHRY98-AUX** instead.
3. **My 2002 Radio does NOT have a Mode button, will this adapter work?**
NO; Radios without "MODE" button are not capable of connecting to this device.
4. **Will I have to disconnect my Satellite Radio or separate CD Changer?**
YES, this adapter uses the 10-pin radio port. Any factory option already in place will need to be disconnected.

Disclaimer

- This product has no affiliation with Chrysler
- We're not liable for misuse of this product.
- We recommend professional installation

email support@discountcarstereo.com

© 1995-Aug-19 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.