



IL-CR12

QUICK START INSTALLTION GUIDE FOR PORSCHE CR1 & CR2 RADIOS

Created: March 21, 2017

Revised: July 17, 2021

PRODUCT SAFETY & DISCLAIMER

READ ALL INSTRUCTIONS CAREFULLY BEFORE INSTALLING, FAILURE TO DO SO MAY CAUSE PERSONAL INJURY OR DAMAGE TO PRODUCT AND/OR PROPERTY

- This installation guide is provided as a GENERAL installation guide, some vehicles vary and may require additional steps. We do not accept responsibility for third party labor charges or modifications. Exercise due-diligence when installing this product.
- We do not accept any responsibility for vehicle damage or personal injury resulting from the installation of this product.

Careless installation and operation can result in equipment damage

Introduction:

For those adamant about keeping their vehicle's stock radio, we offer a simple upgrade that allows the factory radio to support new technology. The IL-CR12 allows Porsche CR-1 & CR-2 cassette radios in the 911, 944, 964, 968, 993 to charge and play music files from Apple's latest iPods, iPhones and Tablets including iPhone 6s, 6+, 7, 12+ etc. Because this adapter connects directly to the radio "CD" port, the factory CD changer (if present), must be disconnected.

Installation:



Although not critical, we recommend disconnecting the car battery. Keep in mind all CR-1/2 radios **are coded** and will not operate without the code. Radio code must be available for radio to operate upon reconnection.

Radio removal required to gain access to connectors.

1. Remove trim ring and ensure both tabs are centered at which point radio is pulled from dash (grasping the cassette opening provides some leverage) or push from rear.

2. With radio removed, disconnect CD changer (if present) 13-pin plug (See **Fig. 1**) from radio.
3. Connect adapter 13-pin plug to "CD" connector on radio (See **Fig. 2**)



Fig. 1
13-pin Plug



Fig. 2
Radio connector

4. Run/route Lightning plug (See **Fig. 3**) to desired mounting location on dashboard, glove box, console etc. (within 4 ft. of radio). **Use caution to not cut, pinch or crimp the cable during this step.**



Fig. 3

5. Securely install lightning plug and cable in a location away from heat, humidity, moving parts, or sharp metal objects. **Damage to lightning plug may occur if subject to abuse.**

Test Operation

1. Turn ignition and radio "ON"
2. Connect Apple IOS device to lightning plug
3. Apple device should begin charging
4. Press "CD" button on radio.
5. Select music track using device built-in controls.



Playlist and Track selection is ***NOT*** possible from the radio
You must use the iPod built-in controls to access music files.

6. Audio device should now be heard on car speakers
7. If successful go ahead and Reinstall the Radio

Important Notes:

1. Vehicle must have a CR1 or CR2 radio. (NOT for CD-1, CD-2 or CD-3)
2. CD changer (if present) must be permanently disconnected.

Disclaimer

- This product has no affiliation with Porsche etc.
- There are no warranties expressed or implied by purchase of this product
- We're not liable for misuse of this product.
- We recommend professional installation.

Email support@discountcarstereo.com

© 1995-July 21 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.