

BECKER



IP-BKRCD/3.5-BKRCD

iPod & AUX Adapter Quick Install Guide for Becker Radios with CD Changer.

Revised: October 18, 2019

Introduction:

These adapters are compatible with any Becker Radio that has a CD Changer connection and particularly great for radios that do not have an AUX menu option including PCMI (BE2580), CR210, CDR210, CR31, CR22, CDR22, CDR21, CR11 etc. **The CD Changer remains connected but will no longer play.**

The **iP-BKRCD** adapter allows users to **connect, play and charge** all Apple 30-pin connecting devices.

The **3.5-BKRCD** adapter allows users to **connect and play** any audio device with a 3.5mm Jack. With the storage capacity of most portable devices sacrificing the CD Changer should be an easy decision.

Installation:



Most Becker radios are coded and will not operate without the code. Do not proceed to step 4 if radio code is not available otherwise radio will not operate upon reconnection.

1. Remove radio from dashboard to gain access to the connectors.
2. Removal tools (See **Fig. 2**) required to remove these radios (except PCMI) and are available separately
3. Slide tools into slots on radio. (Straight edge facing away). Withdraw radio by pulling outwards. To release keys simply press retaining springs. See **Fig. 2**.
For a more detailed radio removal process, click [here](#).
4. With radio removed disconnect yellow (C-1), green (C-2) and blue (C-3) plugs from radio (See **Fig. 1**)

Alert! Yellow plug present only in vehicles with amplifiers; otherwise **C-1** chamber will be empty.




Fig. 1
Radio Connectors



Fig. 2
Radio removal Tools



Fig. 3,
iP-BKRCD



Fig. 4
3.5-BKRCD

5. **IP-BKRCD:**
Connect yellow, blue and green iso plugs (See **Fig. 3**) to **C-1**, **C-2** and **C-3** radio chambers vacated in step 4.

6. Connect factory yellow, blue and green plugs removed in step 4 to the Red 20-pin connector on adapter harness (See **Fig. 3**)
7. **3.5-BKRCD:**
Connect blue iso plug (See **Fig. 4**) to radio chamber **C-1** vacated in step 4.
8. Carefully route 30-pin dock connector OR 3.5mm jack (See **Fig. 5**) to glove box, center armrest or location where the audio device will reside



Fig.5
30-pin dock/3.5mm jack

Test Operation

1. **iP-BKRCD:** Connect Apple 30-pin device (iPod, iPhone) to dock connector
2. Apple device will begin charging
3. **3.5-BKRCD:** Connect audio device to the 3.5mm plug
4. Turn radio "ON" press the **CD** button
5. Select favorite track using audio device built-in controls.



Playlist and Track selection is ***NOT*** possible from the radio. You must use the Audio device built-in controls to access music files.

6. Use radio volume button to set playback level
7. If successful go ahead Re-install the radio. (Removal Tools not required for installation.



These adapters require a working CD Changer to work as described. Porsche **PCMI (BE258D), CR-210, CDR-210, CR-22 and CDR-22** and other Becker radios **do not have AUX ports and therefore requires a CD Changer.**
Do not purchase this part if vehicle does not have a CD Changer.

Disclaimer

- This product has no affiliation with Porsche, Becker or Apple
- We're not liable for misuse of this product.
- We recommend professional installation.

©1995-2019-10-18 Discount Car Stereo. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.