


PDM35 3.5mm Dash Panel Mount Audio Input

3.5 mm Audio Cable • 3.5 mm to RCA Adapter


Peripheral[®]

1 Factory Radio

Connect auxiliary audio interface device** for factory radios.
Use 3.5 mm to RCA adapter if needed to make audio connection.



Radio without SAT Radio or CD Input



Universal Radio Input Interface (sold separately)

Radio with SAT Radio or CD Input



Direct Audio Input Interface (sold separately)

2

Choose mounting position of dash mount audio input and carefully drill 3/8" mounting hole. Install connector.



"factory look" 3.5 mm Dash Panel Mount Audio input (6 ft)

1 Aftermarket Radio

Connect RCA audio connectors to auxiliary audio input on aftermarket radio.



Radio with AUX input




3.5 mm to RCA Adapter

Radio with 3.5 mm input



3.5 mm to Radio Aux

Radio without AUX input



Universal Radio Input Interface (sold separately)

3

Connect your audio device to the newly installed audio input via the supplied 3.5 mm to 3.5 mm connection cable.



3.5 mm to 3.5 mm Audio Cable (4 ft)

* Some radios require the addition of antenna connection adapters

** Aux Audio Interface is sold separately

For best performance have
it professionally installed
Designed for professional installation



Peripheral Electronics[®]
A Division of AAMP of America[™]
13160 56th Court, Clearwater, FL 33760
727-572-9255
support@periphuralelectronics.com
©2009 AAMP of Florida Inc.