



PXDXCH1

Quick Start AUX Adapter Installation Guide for Chrysler, Jeep, Dodge CD Changer Ready Radios

Revised November 27, 2019

Introduction:

Many Chrysler, Dodge and Jeep Owners are looking for a simple and effective way of connecting portable audio devices to the car system. Connecting an auxiliary input adapter to most radios requires disconnecting the CD changer (if present). The PXDXCHI Kit works in select **1995-00 Chrysler Corp vehicles** and provides an input for these owners to connect and play music files from Smartphone, iPod, MP3 player and other portable electronics.

Installation:

Remove radio from dashboard to gain access to connectors. (Vehicle specific radio removal instructions are not part of this guide, but available upon request)

1. If present, disconnect the factory 8- pin plug from radio (See **Fig. 1 & 2**)



Fig. 1
8-pin plug



Fig. 2
radio connector

2. Connect 8-pin plug from adapter harness (See **Fig. 3**) to 8-pin connector on radio (See **Fig.2**)



Fig. 3
installation harness

1. Connect adapter 22-pin Molex plug (See **Fig. 3**) to green module 22-pin Molex connector (See **Fig. 4**)



Fig. 4
22-way Molex connector

Set switches # **1, 4 and # 8** "ON" or down. All others should be "OFF" or Up (See **Fig. 5**)



Fig. 5
dip-switches

2. Connect one of the included audio cables to Module 8-pin DIN connector (See Fig. 6)



Fig. 6
8-pin DIN input

3. Route audio cable 3.5mm plug to front of the dash or location where audio device will reside (within 6 ft.)

Test Operation:

1. Turn ignition and radio "ON"
2. Press "MODE" button on radio to enter CD changer (AUX) Mode
3. Connect audio device to 3.5mm jack on audio device (See Fig. 7).



Fig. 7
3.5mm plug

4. Search audio device for a song and hit play. Music from Audio device will play on car speakers.
5. Use radio volume control button to set the playback level. To reduce distortion, we recommended setting the audio device volume level to 50% or less

Warning! Playlist and Track selection is *NOT* possible from the radio. You must use the audio devices built-in controls to access audio files.

6. If correct operation is confirmed go ahead and reinstall the Radio.

Frequent asked questions

1. Does the PXDXCH1 work on all 1995-02 radios?

NO. The PXDXCH1 works only if the 1995-02 radio has CD changer controls.

CD changer controls radios have the following button indicators:

1. **Mode** button
2. "Disc ^" on preset #1 "Disc ~" on preset #5
3. 5-band Equalizer (See below)



The following radio also has the indicators that point to having CD changer controls:

1. **Mode/Eject** button
2. Direct disc select (1-6) printed above preset buttons
3. Bass & Treble slide controls (See below)



2. My vehicle has the optional CD changer that malfunctions. Will the PXDXCH1 work?

YES; Simply disconnect CD changer from radio and proceed with installation step 1.

3. Does the PXDXCH1 support Bluetooth calls?

NO; but you may enable speakerphone on device and hear caller on car speakers

4. Will I be able to control phone from radio buttons?

NO; radio buttons (except volume) do not apply. Use device built-in control to access and select applications.

** External or remote CD Changer refers to the optional Changer installed on the lower dash, center armrest, hatch, trunk etc. (external CD Changer is not the Changer built-into the head unit)

Call 804-717-5717 or email support@discountcarstereo.com

© 1995-Nov-19 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.