



# PXDXGM2

Quick Start Auxiliary Input Install Guide for select 1995-05 Wired for CD Changer

Revised March 22, 2020

### Introduction:

Many GM Owners are looking for an easy an effective way of connecting and listening to their portable audio devices on the factory radio. Connecting an Auxiliary adapter to most GM's usually requires disconnecting the factory **Slave unit OR CD Changer**\*\*.

The PXDXGM2 connects to the pre-wired 10-pin plug located in trunk/hatch/armrest/glove box etc. and **CD Changer (if present) must be disconnected,** but with the storage capacity of most portable devices, sacrificing the CD changer should be an easy decision.

#### Installation:

- Locate pre-wired 10-pin plug (See Fig. 1) in trunk, hatch, glove box, armrest area of vehicle (radio removal not required)
- 2. If vehicle is equipped with CD changer, disconnect factory 10-pin plug from changer (See. **Fig. 1**)



**Fig. 1** Factory Changer Plug




Fig. 2 mated connectors

3. Connect factory 10-pin plug to the 10-pin connector on installation harness (See Fig. 2 & 3)



**Fig. 3** Adapter harness

4. Connect 22-pin Molex plug on adapter harness (See **Fig. 3**) to 22-pin connector on Module (See **Fig. 4**)



**Fig. 4** 22-pin Molex connector

5. Dip switches **3 & 8** must be "ON" (See **Fig. 5**) **or consult user manual included in kit.** 



**Fig. 5** dip-switches

6. Connect one of two supplied 8-pin **DIN to RCA** OR 8-pin **DIN to 3.5mm** cables to Module. (See **Fig. 6**)



**Fig. 6** 8-pin DIN input

Route the 3.5mm plug toward the dash or location where audio device will reside (within 6 ft.)

## **Test Operation:**

- 1. Turn radio "ON"
- Press "TAPE/AUX", "CD/AUX" or "SOURCE" button on radio to enter AUX Mode
- Connect audio device to 3.5mm plug on 6 ft. Audio cable (See Fig. 6) or RCA jacks.



**Fig. 6** 3.5mm plug

4. Search audio device for a test tack and press play. Music from Audio device will play on car speakers.

5. Use radio volume control button to set playback level. To reduce distortion, we recommended setting audio device volume level to 80% or less.

**Warning!** Playlist and Track selection is \*NOT\* possible from the GM radio. You must use the audio devices built-in controls to access audio files.

\* External or remote CD changer refers to the optional changer installed in lower dash, center armrest, hatch, trunk etc. (external CD changer is not the built-into the radio)

#### Disclaimer

- This product has no affiliation with GM
- We're not liable for misuse of this product.
- •We recommend professional installation.

#### Email support@discountcarstereo.com

© 1995-Mar-20 Discount Car Stereo, Inc. All rights reserved. Information in this document is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.